



FEATURING



Style	Full Height Door
Cabinet Color (exterior/interior)	Black-Faux Stainless/Black
Gross Capacity (cubic feet)	23.41
Gross Capacity (liters)	663.0
Factory Setpoint Temperature °F	35
Factory Setpoint Temperature °C	1.7
Height (inches / cm)	78.75 / 200
Width (inches / cm)	30 / 76.2
Depth less handle (inches / cm)	31.42 / 79.8
Interior LED Light Strips	2
Adjustable Shelves	5
Bottom Shelf	1
Casters	Yes
Volts / Hz / Phase	115 / 60 / 1
Amps	2.4
H.P. (kW)	1/4 (0.19)
Refrigerant	R290
Net Weight (lbs)	340
Net Weight (kg)	154.4
Smartlock Trigger (adjustable)	≥ 41°F (5°C)



Energy Efficiency
Certified



R290 Natural
Refrigerant

Great features. Outstanding value.




Features SMARTLOCK. The first NAMA certified, fully integrated, dual function food health and refrigeration controller.



Brilliant, energy efficient LED lighting creates an impressive visual impact. Standard on all models.



Low-maintenance condenser* helps maintain the merchandiser's performance and reduces the frequency of costly, regular cleaning.



Energy free, Low-E coated glass door for added insulation value.



Programmable Electronic Control Center provides real-time information with audible and visual alarms. Standard on all models.

SMARTLOCK HEALTH TIMER

- Constantly monitors the food storage compartment temperature to ensure it is operating correctly. If the temperature rises above the trigger point for 30 minutes, the unit automatically locks the door preventing access to potentially hazardous food. The unit can be unlocked manually for food inspection.

- The Smartlock system incorporates the reliability of an electronic control module and battery backup to ensure the system functions flawlessly even during a power outage situation.

ENERGY EFFICIENT PERFORMANCE

- Eco-friendly, efficient, self contained R290 refrigeration system delivers setpoint temperatures from 35°F to 37°F depending on your requirements.

- Frost free, forced air system for quick, even cooling with user defined or temperature sensed defrost cycles.

- Electronic microprocessor controller for precise temperature management includes continuous digital temperature display, audible & visual temperature alarm, audible and visual door open alarm.

- Low-maintenance condenser* helps maintain the merchandiser's performance and reduces the frequency of costly, regular cleaning.

- Bottom mount condensing unit provides elevated merchandising visibility keeping products within easy reach.

- High efficiency fan motors maintain optimum air circulation for consistent cabinet temperature.

DURABLE CABINET CONSTRUCTION

- Tough exterior finish to help keep the product looking like new even after years of service.

- 2½" thick walls with high density, foamed in place closed cell insulation for temperature and energy efficiency.

- Black galvanized interior walls with baked on finish that supports product illumination and provides the perfect contrasting backdrop.

- Spacious condenser housing provides superior heat dispersion and air circulation.

- Smooth interior corners for easy cleaning.

- Low profile casters and front levelling legs for easy installation.

CLEAR VIEW GLASS DOOR

- Energy free, Low-E coated, insulated safety glass door helps keep the cold inside.

- Snap-in, one piece, self sealing door gasket makes cleaning trouble-free.

- Self closing torsion bar door helps prevent the door from being left open. The torsion bar system is more durable, reliable and rust resistant than spring loaded systems.

- Ergonomic 18" satin crescent handle.

BRILLIANT CABINET LIGHTING

- Cabinet interior features two (2) full height, high intensity, energy efficient white LED light strips to showcase merchandise and eliminate bulb replacement.


STURDY CABINET SHELVING

- Five (5) coated adjustable shelves resist rust and can be adjusted in 1/2" increments.

- One (1) coated bottom shelf.

ELECTRICAL REQUIREMENTS

- Unit includes cord and plug.

- Dedicated 15 amp grounded 115V 60Hz single phase circuit. 

- NEMA 5-15P three prong 15 amp receptacle.

WARRANTY & CUSTOMER CARE

- One (1) year parts and labor. Additional four (4) years on compressor.

- 24/7 Customer Care support and a network of certified licensed technicians to respond to any refrigeration issue.


ACCESSORIES FOR BRANDING, PROMOTION, CUSTOMIZING PACKOUT



Wire Baskets with Dividers



Wire Shelves



Beverage Pusher



Sandwich Pusher

*Regular condenser cleaning and maintenance not required under normal operating conditions. Some exceptions may apply. Contact Minus Forty for more information.


Warranty is a limited warranty, please refer to detailed warranty outline available from our Customer Care Department. Specifications are subject to change without notice. Weights and dimensions do not include packaging or shipping materials.

All Minus Forty® refrigerators are energy efficiency certified to USA DOE standards for Commercial Refrigerator class.

PRODUCT DIMENSIONS

inches (cm)

FRONT VIEW



SIDE VIEW

