

QBD REFRIGERATION DECK CLEANING INSTRUCTIONS



Why?...Refrigeration deck is the most critical component of the cooler, failure to care of it will not only damage the unit but will also void the manufacturers warranty.

Follow these instructions when performing CD maintenance:

1. Preventive maintenance

- Clean condenser coil with soft brush
- Ensure all drains are free of any debris or impediments
- Check fan motors for normal operation
- Confirm the temperature probe position is correct based on type of cold control in place
- Confirm the appropriate cold control setting is set based on type of cold control in place

2. A Repair (Shop prep)

- Use compressed air gun to clean dirt and debris from the CD
- If further cleaning is required – Use a damp cloth while ensuring that none of the electrical components are exposed to water or moisture. Any usage of water spray or direct water exposure will void the warranty
- Ensure all drains are free of any debris or impediments
- Proceed with cool testing process

3. Refurb process

- Completely remove the cooling deck from the cabinet and identify with asset and serial number
- Use compressed air gun to clean dirt and debris from the CD
- If further cleaning is required – Use a damp cloth while ensuring that none of the electrical components are exposed to water or moisture. Any usage of water spray or direct water exposure will void the warranty
- Ensure all drains are free of any debris or impediments
- Proceed with cool testing process

Please contact the factory if you have any questions or concerns
1-800-663-3005 905-459-0709 info@qbd.com